

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

**METHOD AND APPARATUS FOR USING HYDROXYL TO REDUCE
POLLUTANTS IN THE EXHAUST GASES FROM THE COMBUSTION OF A FUEL**

ABSTRACT OF THE DISCLOSURE

A method and apparatus are provided for reducing pollutants in the exhaust gases produced from the combustion of a fuel by introducing hydroxyl and associated radicals and oxidizers into at least one of the precombustion and postcombustion gas stream of the combustion engine upstream of the catalytic converter and treating the exhaust gases with the catalytic converter.